

SPECIAL FLOORING FOR SPLASH PARK AREAS

AQUASOFT-EX

Innovative, seamless, elastic colorful, anti-slip, long lasting polymer flooring for water parks and splash park areas providing excellent safety and convenience for children and users.

Our water park, splash park flooring is the unique polymeric system for wet areas in constant contact in water or near water continuously.

It provides safety due to its high elasticity and excellent grip while in parallel it has excellent properties and resistance to aggressive chemicals used in water such as chlorine. Great variety in colors as backgrounds and designs that are created to match every possible desire of the end user.

Applied on all aquatic venues such as interactive fountains, splash pads, spray parks, water parks and wet decks.

Steps:

1. POLYSPORT DAMP PROOF BARRIER - PU primer.

Used as water barrier on damp concrete substrates and as an adhesive component between concrete surfaces and sports coatings. Application with roller, brush or squeegee.

2. AQUASOFT 8055 - Specially, modified, two component, polymeric self-leveling coating.

It's solvent free and easy to apply, it shows a good curing behavior even at low or high temperature. Applied with V-notched trowel and a spiked roller.

3. ELASTIC ELEMENTS - Rubber granules.

Granulometry of 0.5mm. Broadcasted on the wet fresh self-leveling surface.

4. AQUASOFT 8055 - Specially, modified, two component, polymeric self-leveling coating.

It's solvent free and easy to apply, it shows a good curing behavior even at low or high temperature. Applied with V-notched trowel and a spiked roller.

5. ELASTIC ELEMENTS - Rubber granules.

Granulometry of 0.5mm. Broadcasted on the wet fresh self-leveling surface.

6. AQUASOFT 8052 - UV-resistant, polymer-based, two-component coating.

It is applied as a final, sealing layer on top of splash park floorings with an airless sprayer or a roller.



AQUASOFT-EX RESINS COLORCHART



ELASTIC ELEMENTS COLORS



Description	Consumption
Polysport Damp Proof Barrier	0,4kg/m ²
Aquasoft 8055	2,15kg/m ²
Elastic elements	1,6kg/m ²
Aquasoft 8055	2,15kg/m ²
Elastic elements	1,8kg/m ²
Aquasoft 8052 colored or Aquasoft 8055 colored	0,4kg/m ²