

PLAYTILE 865

Safety rubber tiles

Safety tiles made of black or colored recycled SBR rubber in thickness from 2.5cm till 10cm and in dimensions of 50X50cm and 100X100cm.

Consist of polyurethane resins and colored recycled SBR rubber. They create a safe flooring for playgrounds and kindergartens, for interior and exterior surfaces. They can be applied easily on stable surfaces of asphalt or cement (with the parallel use of **PU FLEX 140**) or even on compacted fine gravel. They provide excellent shock absorbency, according to European Standards (EN 1177) and BS EN 71-3: 1995.

Thickness: 25mm to 100 mm

Dimensions: 500mm X 500mm, 1000 x 1010 mm

Tile Weight: 5.78 kg (+/- 0.1kg) for 40mm

Tile Colours: Top layer Pigmented: Green / Red (except black)

Tile Colour - Bottom : Black SBR

Material : Full SBR recycled rubber particles

Bottom Drainage: 64 blocks (7 x 7 drainage lines)

Quantity per 1m²: 4 pieces

Critical fall height: 1.3m according to BS EN 1177: 2008

Places of use: universally usable

Installation: full glue down to the ground on bound sub-grounds or side-to-side gluing.

Recommended glues: PU FLEX 140 polyurethane-based glue for total glue-down. Amount needed: app. 500-800 gr/m². For side to side gluing use PU FLEX 140 or alternative.

Tolerances and note about material: Tolerances in thickness: +/- 1 mm,

*Tolerances in measurement: +/- 1 %. Rubber-tiles react to changes in temperature and humidity. This reaction can mostly be prevented by fully adhering the tiles to the ground (cement or asphalt).

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598

Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece



KDF

Sports Flooring Systems & Building Materials
50 YEARS OF EXPERIENCE



The information given here is true, represents our best knowledge and is based not only on laboratory work, but also on field experience. However, because of numerous factors affecting results we offer this information without any guarantee and no patent liability is assumed. For additional information or questions, contact the technical department of KDF LTD.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598

Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece

