

POLTRACK JOGGING TRACK SYSTEM

Certified by Labosport Institute



Elastic, seamless, flexible coloured flooring, ideal for jogging tracks in total thickness of 18mm.

It consists of a shock-pad base of 2 layers. First layer is a mixture of **PU BINDER 1118** and **RECYCLED RUBBER 858**- SBR granules and the second layer is a flexible, colored mixture of **PU BINDER 1118** and **EPDM granules**. Follows the PU self-leveling coating, **POLYSPORT PU 1051** with **EPDM DUST** as a sealing layer and finally the PU, UV-resistant aliphatic top coating, **POLYSPORT 1052**, in two crossing layers.


Steps:

1. **PU PRIMER 870 - Polyurethane primer.**
Applied by airless sprayer or brush.
2. **Mixture of PU BINDER 1118 and RECYCLED RUBBER 858 (in granulometry of 2-5mm or 3-5mm)** applied by paving machine.
3. **Mixture of PU BINDER 1118 and EPDM 856 (in granulometry of 0.5-1.5mm)** applied by paving machine.
4. **Mixture of POLYSPORT PU 1051 and EPDM dust** as a sealing layer for filling the porous of the prefabricated subfloor of sports floorings such as ISOPOL 854 or wet-pour cushion shock-pads. Applied by flat trowel.
5. **POLYSPORT 1052 - UV-resistant, polyurethane, two-component, top coating for outdoor sports floorings.** Applied, in two crossing layers by airless sprayer or a short haired mohair roller.

Concrete surface must be power-trowelled without cracks and must be smooth with a slope of 0.7-1% and humidity under 4% in 10cm depth of concrete.

Generally concrete is a risky sub-floor and there may be problems with rising humidity, especially in areas where the sea level is really high and when the sea is close or in areas near greenery.

Always make expansion joints in large areas of concrete, in order to avoid uncontrollable cracks and failures. Joints should be every 25 square meters creating a grid of 5x5 meters or close to that.



<u>SUBSTRATE REQUIREMENTS</u>	Concrete quality	at least C20/25
	Age:	at least 40 days
	Moisture content:	below 4%

KDF

Sports Flooring Systems & Building Materials
50 YEARS OF EXPERIENCE

Tools:



AIRLESS SPRAYER



BRUSH



PAVING MACHINE



FLAT TROWEL



SANDING
MACHINE



SHORT HAIRD
MOHAIR ROLLER

Colors: Following colorchart.

This is a certified system by Labosport Institute.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr



Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598
Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece



The colors may vary slightly from the original due to digital representation.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598

Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece





The colors may vary slightly from the original due to digital representation.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598
Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece

